



PRODUCT INFORMATION

oilfino Varius G 600 75W-80



DESCRIPTION

oilfino Varius G 600 is a synthetic smooth-running transmission oil for highly loaded manual transmissions for use in commercial vehicles and passenger cars under the highest mechanical and thermal stress. Particularly suitable for use with carbon and molybdenum-coated synchroniser rings of ZF transmissions. By using synthetic base oils and additives tailored to them, today's practical requirements are exceeded.

PROPERTIES

oilfino Varius G 600 offers excellent wear protection and excellent oxidation and temperature stability even under extreme operation and the toughest conditions. The selected base oils with matching additive technology guarantee very good afterflow behaviour at low temperatures and high lubrication safety at high operating temperatures. oilfino Varius G 600 reduces maintenance costs and increases efficiency through extended oil change intervals according to manufacturer's instructions.

SPECIFICATIONS

- API GL-4

RECOMMENDATION

- MAN 341 Typ E3/Z4
- Volvo 97307
- ZF TE-ML 01L
- 02L/ 16K
- Iveco MGS-1

Specific data	Method	Unit	oilfino Varius G 600
SAE grade	SAE J 306		75W-80
Density at 15°C	DIN 51757	kg/m ³	858
Kinematic viscosity at 40 °C	D 445	mm ² /s	57.7
Kinematic viscosity at 100 °C	D 445	mm ² /s	9.6
Viscosity index	D 2270		150
Flash point	D 93	°C	240
Pour point	D 97	°C	-41

All information is provided to the best of our knowledge but without guarantee of any kind. The technical data represent average values and are subject to normal production fluctuations. oilfino reserves the right to improve the products and modify the specification accordingly.